

# MINERVAL<sup>®</sup> E 15

Minerval<sup>®</sup> E15 is an economical and efficient ceiling solution, ideal for all types of rooms.




# Minerval® E 15



## PANEL DESCRIPTION

1:	White decorative glass fiber veil
2:	High density mineral wool panel, 15 mm thick
3:	E edges, painted
4:	Natural glass veil on reverse side



## TYPE OF APPLICATION

- Education
- Office
- Healthcare




## ACOUSTICS

### Sound Absorption

Test results according to EN ISO 354. Classification according to EN ISO 11654.

$\alpha_p$ , Practical sound absorption coefficient



— Eurocoustic Minerval® E 15, 200 mm o.d.s.  
o.d.s = overall depth of system

THK mm	o.d.s. mm	$\alpha_p$ , Practical sound absorption coefficient						$\alpha_w$	Sound absorption class
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz		
15	200	0.30	0.80	1.00	0.85	0.95	1.00	0.95	A



## VISUAL APPEARANCE

Property	White
Light Reflectance (LRV%)	78%
Whiteness (L*)	91%
Gloss (85°)	1.1



## FIRE REACTION

Standard	Class
EN 13501-1	A2-s1,d0



## HUMIDITY RESISTANCE

Class C, relative humidity 95% and 30°C, according to EN 13964:2014.



## INDOOR AIR QUALITY

Certificate / Label	
French VOC	A+



## MATERIAL HEALTH

EUCEB	Eurocoustic panels are manufactured using mineral wool certified by the European Certification Board for mineral wool products (EUCEB), which independently confirms that mineral wool is produced in conformity with the Note Q of European Regulation (EC) No 1272/2008 and therefore classification as a carcinogen does not apply.
REACH	Eurocoustic products comply with the REACH regulation of the European Chemicals Agency and therefore do not contain any Substances of Very High Concern (SVHC) with potential negative impacts on human health or the environment above 100ppm.



## CARBON FOOTPRINT

Life cycle stages A1 to C4 of the EPD, in compliance with ISO 14025 / EN 15804.

	kg CO <sub>2</sub> equiv/m <sup>2</sup>
Minerval E 15	2.29



## CIRCULARITY

Minimum recycled content	51%
Recyclability	Fully recyclable



## CRADLE TO CRADLE CERTIFIED®

This product is Cradle to Cradle Certified® at Bronze level (version 4.0).



## CLEANABILITY

The ceiling surface does not retain dust, which makes the panels easier to clean. The ceiling can be cleaned using a light brush or a vacuum cleaner. This type of cleaning will help extend the service life of the ceilings.



## INSTALLATION

- You are advised to ensure that air can circulate between the rooms and the plenum to balance the temperature and pressures on each side of the ceiling.
- Tiles can be cut with a craft knife without generating any noise or dust.
- The direction in which the panels should be installed is indicated on the back of the panels.
- Contact us if any mineral wool is to be laid in the plenum.



## CE

Eurocoustic ceilings are CE marked according to the European harmonized standard EN13964:2014. CE marked construction products are covered by a Declaration of Performance (DOP) which enables customers and users to easily compare performance of products available on the European market.



## PRODUCT RANGE

Minerval® E 15 ceiling packs are shrink-wrapped for protection. Pallets are wrapped in plastic film and must be stored under cover.

Format	600x600	1200x600
Edge	E	E
Grids	T15 - T24	T15 - T24
Panels/pack	26	16
m <sup>2</sup> /pack	9.36	11.52
Packs/pallet	20	18
Service class	A	C

## COLOURS AND DESIGN

### Color



White