




QUICK-LOCK® T35 CLIP-ON

Visible T-bar systems for lay-in panels are recognized for its superior stability and easy installation. Quick-Lock T35 Clip-on offers a wide range of standard profiles.



Quick-Lock® T35 Clip-on



FIRE REACTION

	Fire standard	Class
Standard colors	EN 13501-1	A1
Special post-painted colors	EN 13501-1	A2



MECHANICAL PROPERTIES

Read more about mechanical properties in the data sheet and DoP, available under downloads



DURABILITY

The system belongs to Class B according to the EN 13964 standard on suspended ceilings.



CARBON FOOTPRINT

Life-cycle stages A1 to C4 from EPD, in conformity with ISO 14025 / ISO 21930 / EN 15804

Product	kg CO2equiv/m
Quick-Lock T35/38 HE MB 3600	1,46
Quick-Lock T35/38 HE CT 600	1,43
Quick-Lock T35/38 HE CT 1200	1,44



CIRCULARITY

Fully recyclable

Recyclability
Fully recyclable



INDOOR AIR QUALITY

Quick-Lock systems are classified A+

Certificate / Label	
French VOC	A+



CE

Quick-Lock grid systems are CE marked according to the European harmonized standard EN13964:2014. CE marked construction products are covered by a Declaration of Performance (DOP) which enables customers and users to easily compare performance of products available on the European market.

COLOURS AND DESIGN

Colors



Snow white