



QUICK-LOCK® INSULA

Quick-Lock Insula is a modular suspension systems for ceiling islands. The system is easy to install and is available in heights of 38, 76 and 91 mm. The system is compatible with both lay-in panels and concealed edges.



Quick-Lock® Insula



FIRE SAFETY

	Fire standard	Class
Grid: Standard colors	EN 13501-1	A1
Grid: Special post-painted colors	EN 13501-1	A2
Edges: (38) standard colors	EN 13501-1	A1
Edges: (38) special post-painted colors	EN 13501-1	A2
Edges: (76, 91) standard & post-painted colors	EN 13501-1	A2



MECHANICAL PROPERTIES

Read more about mechanical properties in the data sheet and DoP, available under downloads



DURABILITY

The system belongs to Class B according to the EN 13964 standard on suspended ceilings.



CARBON FOOTPRINT

Life-cycle stages A1 to C4 from EPD, in conformity with ISO 14025 / ISO 21930 / EN 15804

Product	kg CO2equiv/m
T24/38 Insula 1200	1,20
T24/38 Insula 1800	1,20
T24/38 Insula 2400	1,17
T24/38 Insula 3000	1,16
T24/38 Insula 3600	1,16



CIRCULARITY

Fully recyclable

Recyclability
Fully recyclable



INDOOR AIR QUALITY

Quick-Lock systems are classified A+

Certificate / Label	
French VOC	A+




CE

Quick-Lock grid systems are CE marked according to the European harmonized standard EN13964:2014. CE marked construction products are covered by a Declaration of Performance (DOP) which enables customers and

users to easily compare performance of products available on the European market.

COLOURS AND DESIGN

Colors



Snow white