

TONGA® THERM A



Tonga® Therm A ceiling offers an excellent sound absorption, resistance to bending and thermal resistance, making it ideal for open-space.




Tonga® Therm A



PANEL DESCRIPTION

1:	Decorative glass fiber veil in white or EuroColor
2:	High density stone wool panel, 77 mm thick
3:	A edges
4:	Natural glass veil on reverse side



TYPE OF APPLICATION

- Additional areas
- Education
- Office
- Healthcare




ACOUSTICS

Sound Absorption

Test results according to EN ISO 354. Classification according to EN ISO 11654.

α_p , Practical sound absorption coefficient



— Eurocoustic Tonga® Therm A, 200 mm o.d.s.
o.d.s = overall depth of system

THK mm	o.d.s. mm	α_p , Practical sound absorption coefficient						α_w	Sound absorption class
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz		
77	200	0.66	0.88	0.98	1.05	1.10	1.08	1.00	A



VISUAL APPEARANCE

Property	White 09
Light Reflectance (LRV%)	87%
Whiteness (L*)	94%
Gloss (85°)	1.2



FIRE REACTION

Standard	White 09, EuroColors, EuroDesign	Silver M5
EN 13501-1	Euroclass A1	Euroclass A2-s1,d0



HUMIDITY RESISTANCE

100% flat irrespective of the Relative Humidity.



INDOOR AIR QUALITY

Certificate / Label	
French VOC	A+
Eurofins	Indoor Air Comfort® Gold



MATERIAL HEALTH

C2C Certified Material Health Certificate™	This product has received a C2C Certified Material Health Certificate™ at the Bronze level (standard version 4.0). The C2C Certified Material Health Certificate™ is a verification of the health and safety of a product's composition using the Material Health requirements of the Cradle-to-Cradle Certified Product Standard.
EUCB	Eurocoustic panels are manufactured using mineral wool certified by the European Certification Board for mineral wool products (EUCB), which independently confirms that mineral wool is produced in conformity with the Note Q of European Regulation (EC) No 1272/2008 and therefore classification as a carcinogen does not apply.
REACH	Eurocoustic products comply with the REACH regulation of the European Chemicals Agency and therefore do not contain any Substances of Very High Concern (SVHC) with potential negative impacts on human health or the environment above 100ppm.



CARBON FOOTPRINT

Life cycle stages A1 to C4 of the EPD, in compliance with ISO 14025 / EN 15804.

	kg CO ₂ equiv/m ²
Tonga Therm A	8.69



CIRCULARITY

Minimum recycled content	26%
Recyclability	Fully recyclable



CRADLE TO CRADLE CERTIFIED®

This product is Cradle to Cradle Certified® at Bronze level (version 4.0).



CLEANABILITY

The ceiling surface does not retain dust, which makes the panels easier to clean. The ceiling can be cleaned using a light brush or a vacuum cleaner. This type of cleaning will help extend the service life of the ceilings.



INSTALLATION

- You are advised to ensure that air can circulate between the rooms and the plenum to balance the temperature and pressures on each side of the ceiling.
- Tiles can be cut with a craft knife without generating any noise or dust.
- The direction in which the panels should be installed is indicated on the back of the panels.
- Contact us if any mineral wool is to be laid in the plenum.



THERMAL PROPERTIES

Thermal resistance R = 2.20 m²·K/W (EN 13162).



MECHANICAL PROPERTIES

According to EN 13964 - Annex F, Tonga® Therm A 80 ceilings are classified as C/130N/m² for dimensions 600 x 600 and 1200 x 600. This value should be kept in mind if any mineral wool is to be laid in the plenum.



CE

Eurocooustic ceilings are CE marked according to the European harmonized standard EN13964:2014. CE marked construction products are covered by a Declaration of Performance (DOP) which enables customers and users to easily compare performance of products available on the European market.



PRODUCT RANGE

Tonga® Therm A ceiling packs are shrink-wrapped for protection. Pallets are wrapped in plastic film and must be stored under cover .

Format	600x600	1200x600
Edge	A	A
White 09	•	•
EuroColors	•	•
Grids	T24 - T35	T24 - T35
Panels/pack	12	6
m²/pack	4.32	4.32
Packs/pallet	10	10
Service class	A	A

COLOURS AND DESIGN

Colors



EuroColors

Argile / D1	Calcaire / D2	Craie / D3	Dune / D4	Sable / D5	Terre / D6	Ambre / G1
Emeraud / G2	Grenat / G3	Jade / G4	Rubis / G5	Saphir / G6	Soufre / G7	Topaze / G8
Turquoise / G9	Aluminium / M1	Chrome / M2	Granite / M3	Plomb / M4	Silver / M5	Zinc / M6
Banquise / P1	Crépuscule / P2	Givre / P3	Glacier / P4	Iceberg / P5	Rosée / P6	Céladon / T1
Cuivre / T2	Ocre / T3	Outremer / T4	Sienne / T5	Silex / T6	Ardoise / V1	Basalte / V2
Cobalt / V3	Fer / V4	Lave / V5	Météorite / V6	Noir / V7		