

## DECLARATION OF PERFORMANCE N° 0007-110

- 1. Unique identification code of the product-type: Suspended ceiling: substructure components
- Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): Top fixing (See label)
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Suspended ceiling substructure components
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): SAINT-GOBAIN EUROCOUSTIC 1 place Victor Hugo, 92411 Courbevoie, France www.eurocoustic.com
- Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): Not applicable
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: AVCP System 4 for reaction to fire AVCP System 3 for load bearing capacity AVCP System 4 for durability
- 7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: For the products made up in galvanized steel, it's not required to be tested for reaction to fire; they are classified A1 according to Commission Decision 96/603/CE (AVCP System 4).

The CSTB (n° 0679) performed a determination of the product-type on the basis of type testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product under system 3 for the characteristic load bearing capacity.

It issued tests reports.

A determination of the product-type on the basis of type testing, type calculation, tabulated values or descriptive documentation of the product under system 4 for the characteristic durability was performed. No tasks for the notified body.



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: Not applicable

## 9. Declared performance

| Essential characteristics                   |                     |                                |                                |                         |
|---|---------------------|--------------------------------|--------------------------------|-------------------------|
| Product description                         | Reaction<br>to fire | Load bearing capacity          |                                | Durability:             |
|   |                     | Admissible load<br>(Fadm)<br>N | Ultimate load<br>(Fu)<br>N     | Corrosion<br>protection |
| 14309-ATTACHE TIGRE EP 2 A 8 MM CORRO PLUS  | A1                  | 971 with TC4<br>1563 with TF6  | 2691 with TC4<br>5331 with TF6 | Classe C-D*             |
| 66853 - CHEVILLE BETON SUSP. RAPIDE ET TL34 | A1                  | NPD                            | NPD                            | NPD                     |
| 87457 - EQUERRE AC220 POUR TF DIAM 8MM      | A1                  | 785                            | 6487                           | Classe B                |
| 87502 - PITON ZINGUE FILETE DIAM 6MM        | A1                  | NPD                            | NPD                            | NPD                     |
| 87523 - BASCULE TARAUDEE DIAM 6 AVEC ROSACE | A1                  | NPD                            | NPD                            | NPD                     |
| 87548 - DEMI COLLIER AC22                   | A1                  | 378                            | 3540                           | Classe B                |
| 87550 - EQUERRE ST15 POUR TF DIAM 6MM       | A1                  | 581                            | 2185                           | Classe B                |
| 87551 - CHEVILLE LAITON DIAM 6MM            | A1                  | NPD                            | NPD                            | NPD                     |
| 87554 - ROSACE DIAM 6MM                     | A1                  | NPD                            | NPD                            | Classe B                |
| 87567 - PITON BOIS TARAUDE POUR TF6MM       | A1                  | NPD                            | NPD                            | NPD                     |
| 87568 - PITON BOIS A OEIL POUR TL4MM        | A1                  | NPD                            | NPD                            | NPD                     |
| 87569 - ATTACHE TIGRE PR EPAISSEUR 2 A 8MM  | A1                  | 971 with TC4<br>1563 with TF6  | 2691 with TC4<br>5331 with TF6 | NPD                     |
| 87570 - ATTACHE TIGRE PR EPAISSEUR 8 A 16MM | A1                  | 809 with TC4<br>2334 with TF6  | 2181 with TC4<br>7189 with TF6 | NPD                     |
| 87571 - CLIP SUP HORIZON AC87 4-10MM TF6MM  | A1                  | 1240                           | 3550                           | NPD                     |
| 87572 - CLIP SUP HORIZON AC84 4-10MM TL4MM  | A1                  | 434                            | 1203                           | NPD                     |
| 87573 - CLIP SUP VERT AC264 1,5-5MM TF6MM   | A1                  | 277                            | 905                            | NPD                     |
| 87575 - CLIP SUP HORIZON AC88 10-15MM TF6MM | A1                  | 1268                           | 3457                           | NPD                     |
| 87578 - CLIP SUP VERT AC265 4-10MM TF6MM    | A1                  | 489                            | 1350                           | NPD                     |
| 87579 - CLIP SUP HORIZON AC85 10-15MM TL4MM | A1                  | 450                            | 1187                           | NPD                     |
| 87580 - CLIP SUP HORIZON AC217 4-10MM TF8MM | A1                  | 1132                           | 3411                           | NPD                     |
| 87581 - CLIPSUP HORIZON AC218 10-15MM TF8MM | A1                  | 1353                           | 3804                           | NPD                     |
| 87583 - CLIPSUP HORIZON AC216 1,5-4MM TF8MM | A1                  | 737                            | 2366                           | NPD                     |
| 87584 - CLIP SUP VERT AC266 1,5-5MM TF8MM   | A1                  | 419                            | 1487                           | NPD                     |
| 87585 - CLIP SUP VERT AC267 4-10MM TF8MM    | A1                  | 510                            | 1366                           | NPD                     |

\* Suitable for specific Class D situations, based on an expert opinion (Table 8 in EN 13964: 2014)

All the essential characteristics listed in the first line in this table are corresponding to those described in NF EN 13964:2014.



10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Mr Eric Escalettes Director B.U. Eurocoustic Ceiling Courbevoie, August 29th 2018